

TECHNICAL DATA SHEET

SOLID PANELS / CONTINUOUS LAMELLAS

WOOD SPIECES:

Oak	Rustic Oak	Ash	White Ash
<i>Quercus robur</i>	<i>Quercus robur</i>	<i>Fraxinus excelsior</i>	<i>Fraxinus excelsior</i>

ASSORTMENT DESCRIPTION:

CATEGORY	wood panels
APPLICATION	furniture, construction, stairs, kitchens table tops, worktops, shelves, doors, decorative articles
DIMENSIONS	thickness: 15–45 mm (above 45 mm optionally layered gluing) width: up to 1300 mm length: up to 3000 mm
QUALITY	AA, AB, Rustic – Oak White, Natural – Ash
EDGE GLUING	standard glue D3 – D4 optional
MOISTURE CONTENT	KD 9% +/- 2% according to the standard EN 15497:2014
LAMELLA WIDTHS	70–90 mm (standard) / 40–120 mm (optional)
SANDING	grit 120 (optionally 150)
PROCESSING OPTIONS	cut to size, edge profiling, drilling, machining on CNC, oiling, lacquering
CERTIFICATIONS	FSC, PEFC, EPD
FORMALDEHYDE	in compliance with E1 PN-EN 717-1:2006
BENDING STRENGTH	40 N/mm ² EN 408:2010+A1:2012
BONDING QUALITY	results available on demand / EN13354:2008
REACH	compliant



Edwood Sp. z o.o.
86 Łomaska Street, 21-500 Biała Podlaska, Poland
edwood@edwood.pl | +48 83 342 40 11
www.edwood.pl

